

ET-X11S-01

RG11 Coaxial Cable



Product overview

RG11 is generally used in cable TV and satellite TV. RG11 has the characteristics of high frequency and low loss. The loss is almost the same as that of Rg7 underground cable, but the drop effect is also better.

Construction

Conductor	Material	CCS
	Diameter	1.62mm ± 0.02 mm
	Wire Gauge	14 AWG
Insulation	Material	FPE
	Diameter	7.11 mm ± 0.2 mm
AL Foil	Construction	With Foil
	Material	AP
	Width	24 mm
	thickness	> 0.024 mm
	Overlap Rate	≥ 5%
Braid	Material	AL
	Diameter	0.15 mm
	Braid Coverage	45% - 98%
Jacket	Material	PVC
	Diameter	9.98 mm ± 0.5 mm

Packing

Package length	100m / 300m / 500m
	Customized
Box type	Ordinary / Waterproof
	Customized optional

Test Data

Dielectric Strength	Not breakdown with 2kV DC for 1 min
Sheath Strength	Not breakdown with 3kV
Characteristic Resistance	75Ω ± 5Ω
Insulation Resistance	5000MΩ/km
Elongation at Break (Wire)	≥ 15%
Elongation at Break (Sheath)	≥ 150%
Low Temperature Bending	Not cracked
Thermal Shock	Not cracked
Operating Temperature	- 20°C to +60°C (-4°F to 140°F)
Storage Temperature	- 10°C to +40°C (14°F to 104°F)

Certifications and Standards

Certification	CPR Eca
Executive Standards	Q/DXJ 194-2020

Technical Test [Attenuation @68°F(20°C)]

Frequency(MHZ)	Maximum(dB/100ft)	Maximum(dB/100m)
5	0.38	1.27
55	0.96	3.20
211	1.90	6.33
250	2.05	6.83
270	2.13	7.09
300	2.25	7.49
330	2.35	7.83
350	2.42	8.06
400	2.60	8.66
450	2.75	9.16
500	2.90	9.66
550	3.04	10.12
600	3.18	10.59
750	3.65	12.15
870	4.06	13.52
1000	4.35	14.49